



Certificate No. 1020-CPR-070038635. Annex No. 4

## Technical description of the product

### Metal insulated positive pressure chimneys type SPS IZOL

Nominal diameter of flue liner [mm]	80	100	110	120	130	140	150	160	180	200	225	250	300	350	400	450	500
Thickness of insulation [mm]	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30
Grade of material	1.4404, 1.4301 (1.4307), 1.4521																
Thickness of flue liner [mm]	from 0,40 to 0,60																
Area of flue liner intersection [cm <sup>2</sup> ]	50	78	98	117	135	152	179	203	254	317	399	494	706	968	1262	1597	1970
Maximum load [N/m]	70,0	74,0	78,6	85,5	90,6	93,0	100,6	103,5	118,3	120,2	134,1	151,0	176,3	194,8	226,6	243,5	277,0
Purpose	Drain of combustion products of gas and oil from roomsealed heating appliances, components of flue gas chimney systems type CASCADE and LAS																
Pressure level	Positive pressure, Pressure level: P1																
Max. temperature of exhaust gases (Temperature class)	200°C (T200)																
Condensate resistance *)	working dry - D, working wet - W																
Distance to combustible material	min. 100 mm																
Thermal resistance	0,4 m <sup>2</sup> K/W																
Corrosion resistance	Vm (for grade 1.4521: V1, V2, V3)																
Sootfire resistance	O - not resistant																
Medium height of chimney	14 m																

\*) - in CR established by national regulation – CSN 73 4201, Annex A


**All chimney sections and fittings of Metal insulated positive pressure chimneys type SPS IZOL (made by KOMIN-FLEX) should be designated in accordance with the following designation system:**

**EN 1856-1    T200    P1    W    Vm    L20xxx    O100**

Standard number					
Temperature level (°C)					
Pressure level (positive pressure)					
Condensate resistance (D: dry, W: wet)					
Corrosion resistance (Vm – dec. of material type, V1, V2, V3 – tests)					
Flue liner material specification (L20 - steel 1.4301, thickness of flue liner .0,XX mm)					
Sootfire resistance (O: not resistant), distance to combustible material: min.100					

The stamp of the Notified Body 1020

Ostrava, 11 June 2018



Dipl. Eng. Vojtěch Šebek  
Deputy manager of the Notified Body