



Certificate No. 1020-CPR-070038635, Annex No. 8

Technical description of the product Metal flexible flue liners type STALFLEX

Nominal diameter of flexible flue liner [mm]	80	100	110	120	130	140	150	180	200	250	300
Grade of material									1.4404, 1.4301 (1.4307), 1.4521		
Thickness of flexible flue liner [mm]								0,09; 0,10; 0,12			
Area of flexible flue liner intersection [cm ²]	50	78	98	117	135	152	179	254	317	494	706
Purpose									Drain of combustion products of gas and oil		
Pressure level									Negative pressure, Pressure level: N2		
Max. temperature of exhaust gases (Temperature class)								250°C (T250)			
Condensate resistance *)								working dry - D, working wet - W			
Distance to combustible material								min. 500 mm			
Corrosion resistance							Vm (for grade 1.4521: V1, V2, V3)				
Sootfire resistance							O – not resistant				
Minimum bending radius							2D (D – diameter of flue liner)				
Maximum torque [Nm]							< 50				
Maximum tensile load [kN]							1,0				

*) - in CR established by national regulation – CSN 73 4201, Annex A

All chimney sections and fittings of Metal flexible flue liners type STALFLEX (made by KOMINFLEX) should be designated in accordance with the following designation system:

EN 1856-2	T250	N2	W	Vm	L50xxx	O500
Standard number						
Temperature level (°C)						
Pressure level (negative pressure)						
Condensate resistance (D: dry, W: wet)						
Corrosion resistance (Vm – dec. of material type, V1, V2, V3 – tests)						
Flue liner material specification (L50 - steel 1.4404, thickness of flue liner .0,XX mm)						
Sootfire resistance (O: not resistant), distance to combustible material: min.500						

The stamp of the Notified Body 1020

Ostrava, 11 June 2018



Dipl. Eng. Vojtěch Šebek
Deputy manager of the Notified Body